

# VENF7.EX16189 - Flexible Sprinkler Hose with Fittings Certified for Canada

## Flexible Sprinkler Hose with Fittings Certified for Canada

See General Information for Flexible Sprinkler Hose with Fittings Certified for Canada

### TAIZHOU REALFLEX PIPETEC CO LTD

NO 1 JINNIU RD, HUANGYAN

TAIZHOU, ZHEJIANG 318020 CHINA

EX16189

Model	Rated Pressure, kPa	Max Ambient Temp, °C	Nom Inlet by Outlet Size, in.	Assembly Length, mm	Max No. of 90° Bends	Min Bend Radius, mm	Equivalent Length of 1 in. Schedule 40 Steel Pipe (C = 120), m	Flexibility Type
RF-100 (25/700-1.4-1/2") (unbraided)	1400	66	1 by 1/2	700	2	100	8.2	Limited
RF-100 (25/1000-1.4-1/2") (unbraided)	1400	66	1 by 1/2	1000	3	100	11.3	Limited
RF-100 (25/1200-1.4-1/2") (unbraided)	1400	66	1 by 1/2	1200	3	100	14.9	Limited
RF-100 (25/1500-1.4-1/2") (unbraided)	1400	66	1 by 1/2	1500	3	100	19.2	Limited
RF-100 (25/1800-1.4-1/2") (unbraided)	1400	66	1 by 1/2	1800	4	100	23.8	Limited
RF-100 (25/700-1.4-3/4") (unbraided)	1400	66	1 by 3/4	700	2	100	8.5	Limited
RF-100 (25/1000-1.4-3/4") (unbraided)	1400	66	1 by 3/4	1000	3	100	12.5	Limited
RF-100 (25/1200-1.4-3/4") (unbraided)	1400	66	1 by 3/4	1200	3	100	14.3	Limited
RF-100 (25/1500-1.4-3/4") (unbraided)	1400	66	1 by 3/4	1500	3	100	19.5	Limited
RF-100 (25/1800-1.4-3/4") (unbraided)	1400	66	1 by 3/4	1800	4	100	24.4	Limited
RF-200-700 braided	1400	66	1 by 1/2	700	2	100	7.6	Limited


RF-200-1000 braided	1400	66	1 by 1/2	1000	3	100	10.1	Limited
RF-200-1200 braided	1400	66	1 by 1/2	1200	3	100	11.9	Limited
RF-200-1500 braided	1400	66	1 by 1/2	1500	3	100	15.2	Limited
RF-200-1800 braided	1400	66	1 by 1/2	1800	3	100	17.7	Limited
RF-200-700 braided	1400	66	1 by 3/4	700	2	100	6.4	Limited
RF-200-1000 braided	1400	66	1 by 3/4	1000	3	100	11	Limited
RF-200-1200 braided	1400	66	1 by 3/4	1200	3	100	13	Limited
RF-200-1500 braided	1400	66	1 by 3/4	1500	3	100	15.9	Limited
RF-200-1800 braided	1400	66	1 by 3/4	1800	3	100	19.2	Limited
RF-400-700 braided	1400	66	1 by 1/2	700	2	100	2.5	Limited
RF-400-1000 braided	1400	66	1 by 1/2	1000	3	100	5.5	Limited
RF-400-1200 braided	1400	66	1 by 1/2	1200	3	100	5.8	Limited
RF-400-1500 braided	1400	66	1 by 1/2	1500	3	100	7.4	Limited
RF-400-1800 braided	1400	66	1 by 1/2	1800	3	100	10.1	Limited
RF-400-700 braided	1400	66	1 by 3/4	700	2	100	5.2	Limited
RF-400-1000 braided	1400	66	1 by 3/4	1000	3	100	7.7	Limited
RF-400-1200 braided	1400	66	1 by 3/4	1200	3	100	8.9	Limited
RF-400-1500 braided	1400	66	1 by 3/4	1500	3	100	9.5	Limited
RF-400-1800 braided	1400	66	1 by 3/4	1800	3	100	11.0	Limited
RF-400-700 braided	1400	66	1 by 1	700	2	100	4.9	Limited
RF-400-1000 braided	1400	66	1 by 1	1000	3	100	7.1	Limited
RF-400-1200 braided	1400	66	1 by 1	1200	3	100	7.7	Limited
RF-400-1500 braided	1400	66	1 by 1	1500	3	100	9.2	Limited

RF-400-1800 braided	1400	66	1 by 1	1800	3	100	12.5	Limited
---------------------	------	----	--------	------	---	-----	------	---------

The Series RF-200 flexible sprinkler hose with fittings are intended to be installed with the RF-FK-102 and RF-DK-B bracket assembly in accordance with the manufacturer's installation instructions dated 2019-02-27.

The Series RF-200 flexible sprinkler hose with fittings are intended to be installed with the Fast Center Bracket and S Bracket assembly in accordance with the manufacturer's installation instructions dated 2017-08-15.

These Series RF-400 flexible sprinkler hose with fittings are intended to be installed with the Easy-snap Center Bracket(RF-12320) and Long Side Bracket(RF-12211) assembly in accordance with the manufacturer's installation instructions dated 2019-02-17.

Trademark and/or Tradename: 

Last Updated on 2019-10-18

并不是所有出现在本数据库中的公司名称和产品都满足了UL 跟踪检验服务的要求。只有带有 UL 标志的产品，才应该被视为经过 UL 认证，并满足UL 跟踪检验服务的要求。注意查看产品上的标志。

UL 允许在线认证目录中所含材料的复制遵循以下条件：1.指南信息、装配、构造、设计、系统和/或认证（文件）必须在不篡改任何数据（或图纸）的情况下完整且无误导性地呈现。2.“经 UL 允许从在线认证目录转载”声明必须出现在所摘取材料的邻近位置。此外，转载材料必须包含以下格式的版权声明：“© 2020 UL LLC”